

Everybody strives for, Nobody has achieved yet...

XQ Power series High precision, stiffer rotary Transmission

[High precision, High stiffness, Extra, Compact, Wide reduction range] satisfy all these, so for only SEJINiGB.

※ 자세한 사양 및 외형은 카다로그 참조 바랍니다.

PH-000-M/H/S-S/E-000-S/A-B1/B2/(B3)/C2/S1/S2/EP/(P2)-□□X□□-□□□□□□

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

① **Model name** : PH = Power Hollow

② **Model Number** : Rated output torque (× approximately 10Nm)

③ **Ratio group** : M-Medium ratio, H-High ratio, S-Super ratio

④ **Output bearing type** : S-Standard, E-Enhanced

⑤ **Reduction ratio**

⑥ **Main material** : S-Steel, A-Aluminum (optional)

Optional aluminum material only available with standard output bearing type; please reduce torsional stiffness, tilting rigidity, permitted momentary peak torque as 80% of ratings.

⑦ **Input style** :

PH => B1-Sealed, hollow, direct connecting input structure, without hollow tube, hollow shaft turn by input speed, B2-Sealed, hollow, direct connecting input structure, with hollow tube, hollow tube turn by output speed, C2-Easy to use, clamp input, big input diameter, with sealing, S1-Flange input with sealing, S2-Input shaft with sealing, EP-Elbow Pancake, right angle. Combine with planetary gear at input for ratio higher than 1000 P2, input & output structure in the same side B3 is available as optional for PH.

⑧ 'Insertable input shaft diameter × Applied motor shaft diameter' (If different, applied bushing), or blank (for S1, S2, S3, FS2 input style)

⑨ PH motor code, or blank (for S1, S2, S3, FS2 input style)